

RESPONSE TO OFFICE ACTION
Serial No. 10/628,001
Page 2 of 13

IN THE CLAIMS

1. (Original) A method of evaluating a processing chamber, comprising:
performing a substrate processing operation and a process perturbation operation in a process chamber;
collecting optical emission spectroscopy (OES) data and radio frequency (RF) data during the substrate processing operation and the process perturbation operations; and
performing a multivariate analysis on the collected OES and RF data from the process chamber.
2. (Original) The method of claim 1, wherein the multivariate analysis comprises principle component analysis (PCA).
3. (Original) The method of claim 2, further comprising:
determining if the OES and/or RF data need to be manipulated;
performing the data manipulation; and
performing a multivariate analysis on the revised OES and RF data from the chamber.
4. (Original) The method of claim 3, wherein steady principle components and transitional principle components are identified for the process chamber by principle component analysis.
5. (Original) The method of claim 3, further comprising:
using decomposition of an OES and RF data matrix to yield scores of principle components to determine if the OES and/or RF data need to be manipulated.
6. (Previously Presented) The method of claim 3, further comprising:
enhancing weak signals either by amplifying post perturbation signals, or by selecting a narrower and more sensitive wavelength range or frequency range.

RESPONSE TO OFFICE ACTION
Serial No. 10/628,001
Page 3 of 13

7. (Original) The method of claim 1, further comprising:
using a result of the multivariate analysis to calibrate the process chamber or calibrate another process chamber.
8. (Original) The method of claim 1, further comprising:
using a result of the multivariate analysis to identify a fault in the process chamber or identify a fault in another process chamber.
9. (Original) A method of evaluating a process chamber, comprising:
performing a first substrate processing operation and a first process perturbation operation in a reference chamber;
collecting optical emission spectroscopy (OES) data and radio frequency (RF) data during the first substrate processing operation and the first process perturbation operation;
performing a first multivariate analysis on the collected OES and RF data from the reference chamber to produce first multivariate analysis results;
performing a second substrate processing operation and a second process perturbation operation in a process chamber that is under study, where the first process operation and the second process operation are similar, and the first process perturbation operation and the second process perturbation operation are similar;
collecting OES data and RF data during the second process operation and the second process perturbation operation;
performing a second multivariate analysis on the collected OES and RF data from the chamber under study to produce second multivariate analysis results; and
comparing the second multivariate analysis results from the chamber under study to the first multivariate analysis results from the reference chamber.

RESPONSE TO OFFICE ACTION**Serial No. 10/628,001****Page 4 of 13**

10. (Previously Presented) The method of claim 9 further comprising using a result of comparing the second multivariate analysis results to the first multivariate analysis results to calibrate the chamber under study.

11. (Previously Presented) The method of claim 9, further comprising:
using a result of comparing the second multivariate analysis results to the first multivariate analysis results to identify a fault in the chamber under study.

12. (Original) The method of claim 9, wherein the first and second multivariate analyses comprise principle component analysis (PCA).

13. (Original) The method of claim 9, further comprising:
determining if the OES and/or RF data collected from the reference chamber need to be manipulated;

performing the data manipulation on the data collected from the reference chamber;

performing a multivariate analysis on the revised OES and RF data from the reference chamber; and

manipulating the OES and/or RF data collected from the process chamber that is under study according to the data manipulation scheme developed for the reference chamber.

14. (Original) The method of claim 13, wherein steady principle components and transitional principle components are identified for the reference chamber and the chamber under study by principle component analysis.

15. (Original) The method of claim 13, wherein comparing the results from the first and second multivariate analyses further comprises performing an inner product of the identified principle components for the reference chamber and the chamber under study to generate matching scores.

398536

RESPONSE TO OFFICE ACTION
Serial No. 10/628,001
Page 5 of 13

16. (Original) The method of claim 13, further comprising:
using decomposition of OES and RF data matrixes to yield scores for principle components to determine if the OES and/or RF data need to be manipulated.
17. (Currently amended) The method of claim 13, further comprising:
enhancing [[the]] weak signals either by amplifying post perturbation signals, or by selecting a narrower and more sensitive wavelength range or frequency range.
18. (Original) The method of claim 9, further comprising:
comparing the matching scores to a pre-established matching control limit.
19. (Original) The method of claim 9, wherein the amount of process parameter perturbation is less than 50%.
20. (Original) The method of claim 9, wherein the process chamber is an etching chamber.
21. (Original) The method of claim 9, wherein the process chamber is a deposition chamber.
22. (Original) The method of claim 9, further comprising:
accessing a library of stored diagnosis information; and
searching the diagnosis information to determine a solution to repair the identified fault.
- 23-26. (Withdrawn)

RESPONSE TO OFFICE ACTION

Serial No. 10/628,001

Page 6 of 13

27. (Original) The method of claim 1 further comprising using a result of the multivariate analysis to calibrate the process chamber or calibrate another process chamber.

28. (Original) The method of claim 1 further comprising using a result of the multivariate analysis to identify a fault in the process chamber or identify a fault in another process chamber.

29. (Previously Presented) A method of evaluating a processing chamber, comprising:

performing a substrate processing operation, followed by a process perturbation operation of the substrate process operation in the process chamber;

collecting data of one or more plasma attributes during the substrate processing operation and the following process perturbation operation; and

performing a multivariate analysis on the collected data of plasma attributes.

30. (Previously Presented) The method of claim 29, wherein the one or more plasma attributes are selected from the group consisting of optical electromagnetic emission, RF power, wafer reflectance, process pressure, process temperature, and the combinations thereof.

31. (Previously Presented) The method of claim 29, wherein the one or more plasma attributes are optical electromagnetic emission, RF power, and wafer reflectance.

32. (Previously Presented) The method of claim 29, wherein the plasma attribute is wafer reflectance.

398536

RESPONSE TO OFFICE ACTION
Serial No. 10/628,001
Page 7 of 13

33. (Previously Presented) The method of claim 29, wherein the multivariate analysis comprises principle component analysis (PCA).
34. (Previously Presented) The method of claim 29, further comprising:
determining if the data of plasma attributes need to be manipulated;
performing data manipulation on the data of plasma attributes that are identified to need data manipulation; and
performing a multivariate analysis on the revised data of plasma attributes.
35. (Previously Presented) The method of claim 34, wherein steady principle components and transitional principle components are identified for the process chamber by principle component analysis.
36. (Previously Presented) The method of claim 34, further comprising:
using decomposition of a plasma attributes data matrix to yield scores of principle components to determine if the data of plasma attributes need to be manipulated.
37. (Previously Presented) The method of claim 34, further comprising:
enhancing weak signals either by amplification, or by selecting a narrower and more sensitive wavelength range or frequency range.
38. (Previously Presented) The method of claim 29, further comprising:
using a result of the multivariate analysis to identify a fault in the process chamber or to identify a fault in another process chamber.
39. (Previously Presented) A method of evaluating a process chamber, comprising:
performing a first substrate processing operation, followed by a first process perturbation operation of the first substrate process operation in a reference process chamber;

RESPONSE TO OFFICE ACTION**Serial No. 10/628,001****Page 8 of 13**

collecting data of one or more plasma attributes during the substrate processing operation and the following first process perturbation operation in the reference process chamber;

determining if the collected data of plasma attributes of the first process operation and the first process perturbation operation in the reference process chamber need to be manipulated;

performing data manipulation on the data of plasma attributes of the reference chamber that are identified to need data manipulation;

performing a multivariate analysis on the revised data of plasma attributes of the reference process chamber to produce first multivariate analysis results;

performing a second substrate processing operation, followed by a second process perturbation operation of the first substrate process operation in a process chamber that is under study, wherein the first process operation and the second process operation are similar, and the first process perturbation operation and the second process perturbation operation are similar;

collecting data of one or more plasma attributes during the second substrate processing operation and the following second process perturbation operation in the process chamber that is under study;

performing data manipulation on the data of plasma attributes of the process chamber under study according to the data manipulation scheme used by the reference chamber;

performing a multivariate analysis on the revised data of plasma attributes of the process chamber under study to produce second multivariate analysis results;

comparing the second multivariate analysis results from the chamber under study to the first multivariate analysis results from the reference chamber.

40. (Previously Presented) The method of claim 39, wherein the one or more plasma attributes are selected from the group consisting of optical electromagnetic emission, RF power, wafer reflectance, process pressure, process temperature, and the combinations thereof.

398536

RESPONSE TO OFFICE ACTION**Serial No. 10/628,001****Page 9 of 13**

41. (Previously Presented) The method of claim 39, wherein the one or more plasma attributes are optical electromagnetic emission, RF power, and wafer reflectance.

42. (Previously Presented) The method of claim 39, wherein the plasma attribute is wafer reflectance.

43. (Previously Presented) The method of claim 39 further comprising using a result of comparing the second multivariate analysis results to the first multivariate analysis results to calibrate the chamber under study.

44. (Previously Presented) The method of claim 39, further comprising:
using a result of comparing the second multivariate analysis results to the first multivariate analysis results to identify a fault in the chamber under study.

45. (Previously Presented) The method of claim 39, wherein the first and second multivariate analyses comprise principle component analysis (PCA).

46. (Previously Presented) The method of claim 45, wherein steady principle components and transitional principle components are identified for the reference chamber and the chamber under study by principle component analysis.

47. (Previously Presented) The method of claim 39, wherein comparing the results from the first and second multivariate analyses further comprises performing an inner product of the identified principle components for the reference chamber and the chamber under study to generate matching scores.

48. (Previously Presented) The method of claim 39, wherein determining if the collected data of plasma attributes need to be manipulated further comprising:

398536

RESPONSE TO OFFICE ACTION**Serial No. 10/628,001****Page 10 of 13**

using decomposition of plasma attributes data matrixes for the reference chamber to yield scores for principle components to determine if the data of plasma attributes of the reference chamber need to be manipulated.

49. (Previously Presented) The method of claim 39, wherein the performing data manipulation further comprising:

enhancing the weak signals either by amplification, or by selecting a narrower and more sensitive wavelength range or frequency range.

50. (Previously Presented) The method of claim 47, further comprising:

comparing the matching scores to a pre-established matching control limit.

51. (Previously Presented) The method of claim 39, wherein the first and second process perturbations are performed by varying at least one of the values of the process parameters.

52. (Previously Presented) The method of claim 51, wherein the amount of process parameter variation is less than 50% of the un-perturbed process parameter.

53. (Previously Presented) The method of claim 39, wherein the process chamber is an etching chamber.

54. (Previously Presented) The method of claim 39, wherein the process chamber is a deposition chamber.

55. (Previously Presented) The method of claim 44, further comprising:

accessing a library of stored diagnosis information; and

searching the diagnosis information to determine a solution to repair the identified fault.

398538

RESPONSE TO OFFICE ACTION

Serial No. 10/628,001

Page 11 of 13

56-59. (Withdrawn)

60. (Previously Presented) The method of claim 29 further comprising using a result of the multivariate analysis to calibrate the process chamber or calibrate another process chamber.

61. (Previously Presented) The method of claim 29 further comprising using a result of the multivariate analysis to identify a fault in the process chamber or identify a fault in another process chamber.

398536